



# Gator Prime Self Priming Pump

**Model: GH-3**

**Size: 3" x 3"**

**Model: GH-3**



GATOR PRIME  
GH-3 DATA SHEET

## Data Sheet

Net Weight 214kg (472lbs)

Shipping Weights 225kg (497lbs)

Impeller Dia. 279,4mm (11")

R.P.M. from 850rpm to 2150rpm

Max. Solids 20.63mm (13/16")

## Self Priming

850 rpm 2,3m (7ft) - 1150 rpm 2,9m (9ft)

1450 rpm 4,5m (15ft) - 1750 rpm 7,6m (25ft)

1950 rpm 7,6m (25ft) - 2150 rpm 7,6m (25ft)

## Construction

ALL CAST IRON PARTS ARE ASTM 48, CLASS 30

ALL CARBON STEEL SHAFTS ARE SAE 140 HT

ALL PARTS LABELED CD4 ARE HARDENED 18-8 STAINLESS STEEL,  
CD4, DIN 1-443

ALL PARTS LABELED 31SS ARE CFM

EPOXY AND CERAMIC COATINGS ARE AVAILABLE

THE MECHANICAL SEAL FOR ALL MODELS HAVE A 3166SS BODY,  
VITON O-RINGS AND TUNGSTEN CARBIDE FACES



## THOMAS PUMP-SLIDELL

120 INDUSTRIAL DR.

SLIDELL, LA 70460

985-649-3000 / 985-649-4300 FAX

## THOMAS PUMP-GEORGIA

105 ENTERPRISE AVE.

CARROLLTON, GA 30117

770-908-8000 / 770-908-8008 FAX