



# Gator Prime Self Priming Pump

**Model: GH-6**

**Size: 6" x 6"**

**Model: GH-6**



GATOR PRIME  
GH-6 DATA SHEET

## Data Sheet

Net Weight 413kg (910lbs)

Shipping Weights 437kg (965lbs)

Impeller Dia. 317,5mm (12.1/2")

R.P.M. de 850rpm a 1950rpm

Max. Solids 31,75mm (1.1/4")

## Self Priming

850 rpm 2,4m (8ft) - 1150 rpm 3,0m (10ft)

1450 rpm 4,2m (10ft) - 1750 rpm 4,5m (15ft)

1950 rpm 4,5m (15ft)

## Construction

ALL CAST IRON PARTS ARE ASTM 48, CLASS 30

ALL CARBON STEEL SHAFTS ARE SAE 140 HT

ALL PARTS LABELED CD4 ARE HARDENED 18-8 STAINLESS STEEL,  
CD4, DIN 1-443

ALL PARTS LABELED 31SS ARE CFM

EPOXY AND CERAMIC COATINGS ARE AVILABLE

THE MECHANICAL SEAL FOR ALL MODELS HAVE A 3166SS BODY,  
VITON O-RINGS AND TUNGSTEN CARBIDE FACES



## THOMAS PUMP-SLIDELL

120 INDUSTRIAL DR.

SLIDELL, LA 70460

985-649-3000 / 985-649-4300 FAX

## THOMAS PUMP-GEORGIA

105 ENTERPRISE AVE.

CARROLLTON, GA 30117

770-908-8000 / 770-908-8008 FAX