



Gator Prime Self Priming Pump

Model: GP-10

Size: 10" x 10"

Model: GP-10



GATOR PRIME
GP-10 DATA SHEET

Data Sheet

Net Weight 635kg (1400lbs)

Shipping Weights 663kg (1461lbs)

Impeller Dia. 374,5mm (14.3/4")

R.P.M. from 650rpm to 1450rpm

Max. Solids 76,2mm (3")

Self Priming

650 rpm 2,1m (7ft) - 750 rpm 3,4m (11ft)

850 rpm 4,3m (14ft) - 950 rpm 5,2m (17ft)

1050 rpm 5,5m (18ft) -1150 rpm 5,5m (18ft)

1250 rpm 5,8m (19ft) -1350 rpm 6,7m (22ft)

1450 rpm 6,7m (22ft)

Construction

ALL CAST IRON PARTS ARE ASTM 48, CLASS 30

ALL CARBON STEEL SHAFTS ARE SAE 140 HT

ALL PARTS LABELED CD4 ARE HARDENED 18-8 STAINLESS STEEL,
CD4, DIN 1-443

ALL PARTS LABELED 31SS ARE CFM

EPOXY AND CERAMIC COATINGS ARE AVILABLE

THE MECHANICAL SEAL FOR ALL MODELS HAVE A 3166SS BODY,
VITON O-RINGS AND TUNGSTEN CARBIDE FACES



THOMAS PUMP-SLIDELL

120 INDUSTRIAL DR.

SLIDELL, LA 70460

985-649-3000 / 985-649-4300 FAX

THOMAS PUMP-GEORGIA

105 ENTERPRISE AVE.

CARROLLTON, GA 30117

770-908-8000 / 770-908-8008 FAX