



Gator Prime Self Priming Pump

Model: GP-2
Size: 2" x 2"

Model: GP-2



GATOR PRIME
GP-2 DATA SHEET

Data Sheet

Net Weight 92kg (203lbs)
Shipping Weights 114kg (252lbs)
Impeller Dia. 158,75mm (6.1/4")
R.P.M. from 1150 rpm to 2900rpm
Max. Solids 44,45mm (1.3/4")

Self Priming

1150 rpm 7,3m (24ft) -1450 rpm 7,6m (25ft)
1750 rpm 7,6m (25ft) -2050 rpm 7,6m (25ft)
2350 rpm 7,6m (25ft) -2650 rpm 7,6m (25ft)
2650 rpm 7,6m (25ft) -2900 rpm 7,6m (25ft)

Construction

ALL CAST IRON PARTS ARE ASTM 48, CLASS 30
ALL CARBON STEEL SHAFTS ARE SAE 140 HT
ALL PARTS LABELED CD4 ARE HARDENED 18-8 STAINLESS STEEL,
CD4, DIN 1-443
ALL PARTS LABELED 31SS ARE CFM
EPOXY AND CERAMIC COATINGS ARE AVILABLE
THE MECHANICAL SEAL FOR ALL MODELS HAVE A 3166SS BODY,
VITON O-RINGS AND TUNGSTEN CARBIDE FACES



THOMAS PUMP-SLIDELL

120 INDUSTRIAL DR.
SLIDELL, LA 70460
985-649-3000 / 985-649-4300 FAX

THOMAS PUMP-GEORGIA

105 ENTERPRISE AVE.
CARROLLTON, GA 30117
770-908-8000 / 770-908-8008 FAX