



Gator Prime Self Priming Pump

Model: GP-4

Size: 4" x 4"

Model: GP-4



GATOR PRIME
GP-4 DATA SHEET

Data Sheet

Net Weight 259,5kg (600lbs)

Shipping Weights 280kg (614lbs)

Impeller Dia. 247,65mm (9.3/4")

R.P.M. from 650rpm to 1950rpm

Max. Solids 76,2mm (3")

Self Priming

650 rpm 1,5m (5ft) - 750 rpm 2,4m (8ft)

850 rpm 4,9m (16ft) - 950 rpm 5,8m (19ft)

1050 rpm 6,7m (22ft) -1150 rpm 7,3m (24ft)

1250 rpm 7,6m (25ft) -1350 rpm 7,6m (25ft)

1450 rpm 7,6m (25ft) -1550 rpm 7,6m (25ft)

1650 rpm 7,6m (25ft) -1750 rpm 7,6m (25ft)

1850 rpm 7,6m (25ft) -1950 rpm 7,6m (25ft)

Construction

ALL CAST IRON PARTS ARE ASTM 48, CLASS 30

ALL CARBON STEEL SHAFTS ARE SAE 140 HT

ALL PARTS LABELED CD4 ARE HARDENED 18-8 STAINLESS STEEL,
CD4, DIN 1-443

ALL PARTS LABELED 31SS ARE CFM

EPOXY AND CERAMIC COATINGS ARE AVILABLE

THE MECHANICAL SEAL FOR ALL MODELS HAVE A 3166SS BODY,
VITON O-RINGS AND TUNGSTEN CARBIDE FACES



THOMAS PUMP-SLIDELL

120 INDUSTRIAL DR.

SLIDELL, LA 70460

985-649-3000 / 985-649-4300 FAX

THOMAS PUMP-GEORGIA

105 ENTERPRISE AVE.

CARROLLTON, GA 30117

770-908-8000 / 770-908-8008 FAX