



Gator Prime Self Priming Pump

Model: GP-6

Size: 6" x 6"

Model: GP-6



GATOR PRIME
GP-6 DATA SHEET

Data Sheet

Net Weight 364kg (802lbs)
Shipping Weights 391kg (862lbs)
Impeller Dia. 314,32mm (12.3/8")
R.P.M. from 650rpm to 1550rpm
Max. Solids 76,2mm (3")

Self Priming

650 rpm 2,4m (8ft) - 750 rpm 2,7m (9ft)
850 rpm 3,6m (12ft) - 950 rpm 4,2m (14ft)
1050 rpm 5,5m (18ft) -1150 rpm 6,4m (21ft)
1250 rpm 6,4m (21ft) -1350 rpm 6,7m (22ft)
1450 rpm 7,0m (23ft) -1550 rpm 7,6m (25ft)

Construction

ALL CAST IRON PARTS ARE ASTM 48, CLASS 30
ALL CARBON STEEL SHAFTS ARE SAE 140 HT
ALL PARTS LABELED CD4 ARE HARDENED 18-8 STAINLESS STEEL,
CD4, DIN 1-443
ALL PARTS LABELED 31SS ARE CFM
EPOXY AND CERAMIC COATINGS ARE AVILABLE
THE MECHANICAL SEAL FOR ALL MODELS HAVE A 3166SS BODY,
VITON O-RINGS AND TUNGSTEN CARBIDE FACES



THOMAS PUMP-SLIDELL

120 INDUSTRIAL DR.
SLIDELL, LA 70460
985-649-3000 / 985-649-4300 FAX

THOMAS PUMP-GEORGIA

105 ENTERPRISE AVE.
CARROLLTON, GA 30117
770-908-8000 / 770-908-8008 FAX