



# Gator Prime Self Priming Pump

**Model: GP-8**

**Size: 8" x 8"**

**Model: GP-8**



**GATOR PRIME  
GP-8 DATA SHEET**

## **Data Sheet**

Net Weight 581kg (1295lbs)

Shipping Weights 634kg (1399lbs)

Impeller Dia. 374.65mm (14.3/4")

R.P.M. from 650rpm to 1350rpm

Max. Solids 76,2mm (3")

## **Self Priming**

650 rpm 2,7m (9ft) - 750 rpm 3,7m (12ft)

850 rpm 4,6m (15ft) - 950 rpm 5,2m (17ft)

1050 rpm 6,1m (20ft) - 1150 rpm 6,4m (21ft)

1250 rpm 6,7m (22ft) - 1350 rpm 7,0m (23ft))

## **Construction**

ALL CAST IRON PARTS ARE ASTM 48, CLASS 30

ALL CARBON STEEL SHAFTS ARE SAE 140 HT

ALL PARTS LABELED CD4 ARE HARDENED 18-8 STAINLESS STEEL, CD4, DIN 1-443

ALL PARTS LABELED 31SS ARE CFM

EPOXY AND CERAMIC COATINGS ARE AVAILABLE

THE MECHANICAL SEAL FOR ALL MODELS HAVE A 3166SS BODY, VITON O-RINGS AND TUNGSTEN CARBIDE FACES



## **THOMAS PUMP-SLIDELL**

120 INDUSTRIAL DR.

SLIDELL, LA 70460

985-649-3000 / 985-649-4300 FAX

## **THOMAS PUMP-GEORGIA**

105 ENTERPRISE AVE.

CARROLLTON, GA 30117

770-908-8000 / 770-908-8008 FAX